

LR-FB20BB

HEAVY DUTY LEAD
FILTRATION CARTRIDGE



LR-FB20BB

HEAVY DUTY LEAD FILTRATION CARTRIDGE



APPLICATIONS

- ▶ **Whole House**

FEATURES • BENEFITS

- ▶ Professional grade lead **reduction system**
- ▶ **NSF/ANSI Standard 53 certified** to reduce cysts such as Cryptosporidium and Giardia by mechanical means
- ▶ **Fibredyne technology** provides minimal loss of water pressure, even during times of high consumption.
- ▶ **Whole-House Protection:** Ensures clean, lead-free water from every tap, protecting your family from harmful contaminants
- ▶ Fibredyne cartridge technology enables **2x the flow efficiency of comparable competitive lead filters**

INSTALLATION TIPS

- ▶ Choose a mounting location suitable to support the full weight of the system when operating.
- ▶ Make sure to properly lubricate o-ring prior to use.
- ▶ Install vertically with bowl hanging down.
- ▶ Allow 2-1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.

OPERATION TIPS

- ▶ Replace cartridge if flow rate decreases.
- ▶ Do not exceed service flow rate.
- ▶ Inspect o-ring during each cartridge change. Lubricate and/or replace if necess

SPECIFICATIONS

- ▶ Model/Part Number: LR-FB20BB / 655210-43
- ▶ Filter Type: Fibredyne® Carbon Block 4"x20"
- ▶ Micron Rating: 0.5 microns
- ▶ Capacity: 151.000 L (40,000 gallons)
- ▶ Flow Rate: Up to 38 L/min (10 GPM)
- ▶ Pressure Range: 2 - 6.2 bar (30 -90 PSI)
- ▶ Temperature Range 4.4° -37.8°C (40° -100°F)
- ▶ Filter Life* 4 - 5 months
- ▶ Contaminant Reduction: Lead, Cyst: NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.



System LR-50BB with cartridge 655210-43 Tested and Certified by NSF International against CSA B483.1 and NSF/ANSI Standard 53 for the reduction of Lead and Cyst.